

5

**DETACHABLE COIL FOR
ANEURYSM THERAPY**

TO THE COMMISSIONER OF PATENTS AND TRADEMARKS:

Your petitioners, Stephen C. Jacobsen, John Lippert, Clark C. Davis, and Kent Backman, citizens of the United States and residents of Utah, whose post office and residential addresses are 274 South 1200 East, Salt Lake City, Utah 84102; 9006 North Jeremy Circle, Park City, Utah 84098; 4564 Wallace Lane, Salt Lake City, Utah 84117; and 3299 Splendor Way, Salt Lake City, Utah 84124; respectively, pray that letters patent may be granted to them as inventors of the improvement in a **DETACHABLE COIL FOR ANEURYSM THERAPY** as set forth in the following specification.

5/18

This application is a continuation-in-part of co-pending Application Serial Number 09/023,806 which was filed on February 13, 1998.

BACKGROUND OF THE INVENTION

1. Field of the Invention

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000

The present invention relates to endovascular devices for occluding and/or stabilizing and sealing off vasculature or body passageways, tissue defects, and aneurysms. More specifically, the present invention relates to a method and apparatus for threading wires into body cavities and detaching end sections thereof using vibrational energy, for example, in the form of elastic waves.

2. State of the Art

A variety of methods have been developed for occluding and/or stabilizing and sealing off vasculature or body passageways, tissue defects and aneurysms with the use of endovascular catheters including injectable particles, injectable glue, and detachable coils and other devices. The use of detachable coils appears to be gaining widest acceptance for aneurysm therapy, perhaps because of the ease and precision of control of the delivery and disposition of the coil at the desired occlusion site.

One approach for delivering and detaching coils at an occlusion site involves forming or attaching the coil at the distal end of a wire, and then threading the coil and wire through a catheter until the coil is disposed at the occlusion site. An electric current is then applied to the proximal end of the wire and conducted through the wire to the

point of origin or attachment of the coil where it causes the coil, for example, by electrolysis, to detach from the wire. See US Patent Nos. 5,569,245, 5,624,449, 5,122,136, 5,540,680, and 5,354,295.

Among the problems associated with the electrically detachable coil approach is the time necessary to effectuate detachment (which changes with increasing number of devices delivered), the lack of reliability that the coil will detach, discomfort with the use of a grounding needle (insertable in the flesh of the patient) required for the proper functioning of the device, generation of particulates from the detachment site (electrolysis), and inability to select the size of the coil in vivo.

OBJECTS AND SUMMARY OF THE INVENTION

It is therefore an object of the invention to provide an apparatus and method for selectively detaching an end section of a wire in a body passageway by non-electrical means.

It is another object of the invention to provide such an apparatus and method in which the end section of the wire may be quickly and reliably detached, independently of the number of devices delivered.

It is a further object of the invention to provide such an apparatus and method in which little discomfort results to the patient.

It is still another object of the invention to provide such an apparatus and method, in accordance with one aspect thereof, in which multiple sections of the end segment of the wire may each be selectively detached at different times.

It is an additional object of the invention to provide such an apparatus and method, in accordance with another aspect thereof, in which it may readily be determined by the user when the end section of the wire has detached.

It is a further object of the invention to provide such an apparatus and method in which little preparation of the wire and end section is required to allow for subsequent use and detachment of the end segment.

It is still another object of the invention to provide such an apparatus and method in which therapeutic fluid may be delivered along with the wire to a target body location.

The above and other objects of the invention are realized in a specific illustrative embodiment of a wire apparatus with a detachable distal end which includes an elongate wire (either solid or hollow) having a distal end section, and a discontinuity located rearwardly of the distal end section for rupturing when vibrational energy is applied thereto. The apparatus includes a delivery means coupled to the elongate wire for delivering therapeutic fluid to a target body location and a vibrational energy generator, preferably an ultrasound generator, for applying vibrational energy to the wire to travel to the discontinuity to cause detachment of the distal end section. The vibrational energy may comprise axial or torsional waves mechanically induced into the wire.

In use, the wire is threaded through a vasculature or body passageway to a target location, and therapeutic fluid is injected through a catheter or hollow wire to the target location. Then vibrational energy is applied to the wire to cause the distal end section to detach and remain at the target location to occlude the passageway, and the remainder of the wire is withdrawn from the patient.

In accordance with one aspect of the invention, the discontinuity could include a cut in the wire, a hole, a reduced diameter section, an abrupt increase in mass, an adhesive, soldered or spot-welded joint which joins the distal end section to the wire, a coil soldered or adhesively attached to either the outer surface of a solid or hollow wire, or to the inner surface of a hollow wire, or a heat or chemically treated section. Alternatively, the distal end section could include a plurality of discontinuities, each adapted to rupture at a different vibrational levels or frequencies, to detach a selected portion of the distal end section which is distal to the discontinuity being ruptured.

Other objects, features and advantages of the invention will become apparent from a consideration of the following detailed description presented in connection with the accompanying drawings

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a side, fragmented, cross-sectional view of a wire made in accordance with the principles of the present invention, in which the proximal end of the

wire is coupled to an ultrasound generator and the distal end of the wire is formed into a tangled mass disposed in an aneurysm;

FIGS. 2-3, 4A-4C, and 5-6 show side, fragmented views of different embodiments for providing discontinuities to allow detachment of end coil sections from delivery wires, all in accordance with the principles of the present invention;

FIG. 7 is a side, fragmented view of a hollow end coil section having a plurality of discontinuities for tuned resonator detachment, in accordance with the principles of the present invention;

FIGS. 8 and 9 show side, fragmented views of embodiments of guide wire/catheter combinations where friction between the guide wire and catheter is minimized;

FIG. 10 is a graphic view of a wire illustrating nodal points responsive to different vibrational frequencies for detachment of end sections;

FIGS. 11A-11C show side views of different embodiments of the invention having a hollow wire and a mass or group of masses disposed on adjacent or opposite sides of a cut in the hollow wire;

FIGS. 12A-12B show sectional views of different embodiments of a hollow wire with a coil mass disposed adjacent a cut in the wire that does not extend entirely through the outer wall of the wire.

FIG. 13 shows a cut-away view of a catheter and guide wire combination with a wide cut to allow fluid to pass through the slot and out the distal end;

1073996-2449
15
20

FIG. 14 is a cross-section view of the catheter and guide wire combination showing the adhesive joint between the guide wire and the distal end of the wire and the fluid passage through the mass in the distal end;

FIG. 15A depicts a system for determining when detachment of the distal end has occurred; and

FIGS. 15B and 15C show a plot of impedance (z) versus frequency before and after detachment, respectively.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Reference will now be made to the drawings in which the various elements of the present invention will be given numeral designations and in which the invention will be discussed so as to enable one skilled in the art to make and use the invention.

Referring to FIG. 1, there is shown a side, cross-sectional view of a blood vessel 4 in which an aneurysm 8 is shown formed in one side of the vessel. A fragmented view of a catheter 12 is shown threaded in the vessel 4, with a terminal end 12a positioned adjacent the aneurysm 8. Threaded through the catheter 12 is a wire 16, which extends entirely through the catheter 12 and out the terminal end 12a into the aneurysm 8 (or the entrance thereof) to substantially fill the aneurysm with a coiled end section 16a. Wire 16 may be any long prismatic element, whether solid or hollow, and the end section 16a could be tangled, formed into specific shapes, etc. as well as being coiled.

A discontinuity 20 is formed between the end section 16a of the wire and the rest of the wire 16. The discontinuity 20 may take a variety of shapes and forms, so long as it is designed to rupture, break or separate when vibrational energy of a certain frequency and magnitude is applied to the wire 16. The vibrational energy source in the FIG. 1 embodiment is preferably an ultrasound generator 24, but could be something as simple as a striker, mallet, hammer, etc. for striking the wire 16 to cause mechanical vibrations to propagate to the discontinuity 20.

In use, the catheter 12 is threaded through a vasculature or body passageway to a site at which the end section 16a of the wire is to be disposed, such as the aneurysm 8 in FIG. 1. The purpose of such disposal, for example, is to provide an occlusion in the passageway to allow for coagulation of blood to prevent further flow, or, as in the FIG. 1 schematic, to cause scarring in the aneurysm 8 to thereby fill the aneurysm with scar tissue to prevent the bursting thereof, etc. The end section 16a is shown as being coiled or tangled but when threaded through the catheter 12 it would be straightened. Formation of a wire or coil with these properties is frequently accomplished by heat treating or other methods known in the art. Then when the end section 16a is pushed out the terminal end 12a of the catheter, the end section would resume the normally coiled or tangled condition as shown (enhanced also by body warmth).

After the end section 16a has been guided to the desired target site, the ultrasound generator 24 would be connected to the proximal end of the wire 16 and an ultrasound signal applied thereto. The frequency and amplitude of the signal (observed on a

spectrum analyzer 28) would be selected to produce high stress in the discontinuity 20, fatiguing the wire so that it breaks, ruptures, or otherwise separates at the discontinuity, leaving the end section 16a in the aneurysm 8. Because the system uses vibrations in the ultrasonic range, the separation is accomplished rapidly, reliably and without pain to the subject. A more detailed diagram of the vibrational energy system and method are provided in FIG. 15A, described below.

FIG. 2 shows a fragmented, side, cross-sectional view of a wire 30 made, for example, of stainless steel, connected to a tubular end section 34 made, for example, of nickel titanium alloy or platinum. The terminal end of the wire 30 is tapered, as shown, and is inserted into a hollow 34a in the proximal end of the end section 34, and there secured by an adhesive, solder, or weld 35. A coil 36 made, for example, of stainless steel is soldered, welded or otherwise attached to the terminal end of the wire 30 to enhance the bond between the wire and the end section 34.

The end section 34 includes a plurality of cuts 37 made to extend generally transversely in the end section and provided to shape the end section into a coiled or tangled configuration, and to allow for more surface area exposure of the end section to blood for inducing clotting. See co-pending US patent application no. 08/568,493, filed December 7, 1995, for a further discussion of the employment of cuts in wire to allow flexibility and control shape while maintaining torquability. Two or more cuts 38 (rotated 90 degrees with respect to one another) are shown spaced rearwardly from the plurality of cuts 37 by a distance greater than the spacing between the cuts 37, and are

provided to serve as the discontinuity for rupturing (through fatigue) when the vibrational signal is applied to the wire 30. The cuts 38, of course, could be formed at the same time as the other cuts 37 but, for example, would be made deeper (creating a thinner beam), wider (creating a longer beam), or adjacent a mass 39 disposed in the end section 34, or a combination of these, to sever or rupture when the vibrational signal is applied to the wire 30.

FIG. 3 shows a fragmented, side, cross-sectional view of another embodiment of a wire with a discontinuity in accordance with the present invention. Here, a wire 40 made, for example, of stainless steel, is fitted into the hollow 44a of an end section 44 made, for example, of nickel-titanium alloy. The wire 40 would be held in place in the hollow by a suitable adhesive, such as epoxy or cyanoacrylate. A plurality of cuts 48 are made in the end section 44 to provide for coiling and shaping the end section as desired for ultimate disposition at a target site in a body passageway. A cut or diameter reduction 49 is also formed in the wire 40 to provide the desired discontinuity. A coil mass 47 might also be added about the wire 40 to further exaggerate the discontinuity. The cut 49 might advantageously be about 1/2 of the way through the wire 40 in the transverse direction to serve to rupture or separate when an ultrasound signal is applied to the wire.

FIG. 4A shows another embodiment of a discontinuity between a wire 50 and an end section 54, again including cuts 58. The terminal end of the wire 50 is attached by a section of adhesive 59 to the proximal end of the end section 54. The adhesive 59 is selected from materials that are somewhat brittle, such as sodium silicate, so that when an

ultrasound signal is applied to the wire 50, the adhesive 59 will fracture to allow the end section 54 to separate from the wire 50. Alternatively, section 59 of wire 50 could be heat-treated or H+ embrittled to make the wire brittle at that location. As yet another alternative, section 59 could be chemically-treated, such as by etching, to make the wire weaker at that location.

FIG. 4B shows the discontinuity formed as a hole 51, whereas FIG. 4C shows the discontinuity as a spot weld 53 joining the wire 55 side-by-side to an end section 56. A coil mass 57 provides additional discontinuity. The process of spot welding heats the wire 55, making it more susceptible to fatigue and breaking. In fact, heating alone may be used to create a "discontinuity".

FIG. 5 shows an embodiment similar to that of FIG. 3 except that the discontinuity does not comprise a cut in either the wire 60 or end section 64. Rather, the discontinuity is formed at the joint or connection between the wire 60 and end section 64 wherein the wire is inserted in the hollow 64a of the end section and held in place by a blood soluble adhesive 68, such as sodium silicate. When the end section 64 is guided through a blood vessel by the wire 60 (i.e., through a catheter inserted in a blood vessel), blood enters the hollow 64a of the end section 64 which, along with blood contacting the adhesive 68 at the proximal end of the end section, operates to dissolve the adhesive and allow separation of the end section from the wire.

Application of a vibrational signal such as an ultrasound signal to the wire 60 accelerates the dissolution and ultimate separation of the end section 64 from the wire 60

to allow disposition of the end section at the target site. In effect, two mechanisms may be employed to cause separation--providing greater security and safety in ensuring separation.

5 The FIG. 6 embodiment includes a wire 70 at the distal end of which is disposed a heavy mass of material 74, preferably wound about the distal end. For example the mass 74 might include windings of platinum. The abrupt transition from the wire 70 to the heavy mass 74 provides a discontinuity at location 78 just behind the mass so that when vibrational energy of a certain frequency and amplitude is applied to the wire, the wire is caused to break at the discontinuity or stress point 78, releasing the mass 74 at a target site in a body passageway. The wire 70 might also be made of platinum, stainless steel or nickel titanium alloy.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

FIG. 7 shows an embodiment of a detachable wire 80 having a plurality of longitudinally spaced cuts 84 in sections 86 and 88, which act as separate discontinuities. Each of the discontinuities 84 of section 86 are formed or "tuned" with a predetermined depth, width, and/or spacing to rupture in response to different amplitudes and frequencies of vibrational energy than the discontinuities of section 88. In this manner, the user can selectively apply vibrational energy to the wire 80 to cause a selected section of the discontinuities 84 to rupture. Such rupturing can take place successively to deposit lengths of wire at different locations in a body passageway or to deposit all of the lengths (to serve as emboli) at a single location. The "tuning" of the discontinuities 84 is both a function of the characteristics of the cuts, and also of the segment lengths between the

discontinuities. Such timing could be used to "deposit" great numbers of particles such as for AVM therapy.

5 The ultrasonic vibrational energy can be transmitted down the wire in two different modes of propagation: axial or torsional. In the axial mode, the wire is alternately placed in tension and compression along the axis of the wire as the wave travels. In the torsional transmission mode, the wire is alternately placed in clockwise and counterclockwise torsion about its axis as the wave travels. Both modes are useful.

20 The detachment sites shown and described above are configured for detachment in the axial mode. However, torsional waves are advantageous when using a section of wire which has been provided with cuts to enhance its lateral flexibility. The cuts severely reduce the axial stiffness of the wire (particularly of hollow wire), but can be made in such a way as to not reduce the torsional stiffness of the wire as much. (See, e.g. U.S. Patent Application Ser. No. 08/568,493, filed Dec. 7, 1995). The cut wire therefore is more capable of transmission of torsional than of axial vibration. Where selective detachment is desired, the wave is required to travel through sections of cut wire to reach the various detachment sites. Consequently, the torsion mode is preferred for selective detachment of cut wire.

20 The cuts 84 create spring elements to isolate the intermediate uncut sections of the wire 80 which have a mass. When a vibrational energy wave at the resonant frequency of the spring/mass system is applied to the wire 80, the wire is excited longitudinally and the sections of mass between the cuts vibrate longitudinally at high amplitude which fatigues

the spring elements (location of cuts) causing them to break. The wire 80 could advantageously be made of stainless steel or nickel titanium alloy.

FIGS. 8 and 9 show side, cross-sectional, fragmented views of a type of wave guide construction for transmitting vibrational energy along a wire surrounded by a catheter or sleeve. Referring to FIG. 8, there is shown a wire 90 disposed inside of a catheter or sleeve 94 but held out of touch from the sleeve by supports, for example, in the form of rings spaced apart longitudinally and uniformly along the length of the wire and sleeve. The supports 98 are positioned at the velocity nodal points of the vibrational energy waves which are transmitted along the wire/sleeve combination to cause detachment of an end section (not shown). The velocity nodal points, of course, are those locations in a mechanical wave where there is little or no movement or velocity of the wave-carrying structure, whereas the locations midway between the supports 98 are the antinodes where there is maximum movement of the wave-carrying structure. By providing the supports 98, the wire and sleeve are held apart to thereby prevent friction between the two as the vibrational energy wave travels down the wire/sleeve combination. Thus, little energy is lost along the length of the wire and sleeve and so detachment of the end section would take less time.

FIG. 9 is a side, cross-sectional, fragmented view of a wire 100 about which is disposed a sleeve 104 and between which is disposed a hydrophillic coating, elastomeric material, or lubricant 108 to allow the wire and sleeve to move relative to one another without significant friction and thus without loss of vibrational energy.

FIG. 10 shows a graphic representation of a wire 110 having discontinuities 114, 118 and 122 spaced longitudinally along the wire. Graphically superimposed over the wire 110 are three vibrational energy waves 114a, 118a, and 122a. In order to cause the wire 110 to separate at one of the selected discontinuities, a vibrational energy wave is applied to the wire so that the nodal point of the wave falls at the desired discontinuity. A vibrational energy wave causes mechanical resonance in the longitudinal direction where nodal points fall at locations which are spaced every one half of the wavelength. As briefly mentioned earlier, at the nodal points along the wire, the velocity or movement of the wire is minimal, but the stress is maximal. Consequently, by applying a vibrational energy wave such as wave 114a to the wire 110, the wire would be caused to separate at that location where the greatest stress is occurring and the wire is weakest, because a nodal point of wave 114a occurs at discontinuity 114. Similarly, if it were desired that the separation occur at discontinuity 118, then vibrational energy wave 118a would be applied to the wire, etc. In the manner described, appropriate mechanical energy waves can be applied to wires to cause separation at selected discontinuities along the wire. The various embodiments described above can be used to occlude blood flow, create scar tissue in aneurysms, in a known manner, or the embodiments could also be used to detach any type of end section device, such as a tubal block; in a body passageway, for example, a fallopian tube; to block passage of eggs; or detach elements containing drugs for delivery to a target site; etc. That is, the embodiments are not limited solely to use in vasculature passageways.

FIG 11A shows a side view of another embodiment of a wire with a discontinuity in accordance with the present invention. Here, a wire 200, made, for example, of stainless steel, is hollow, allowing therapeutic fluid and drugs to pass therethrough. A plurality of cuts (not shown) may be made in the end section 201 to provide for coiling and configuring the end section as desired for ultimate disposition at a target site in a body passageway. A cut or diameter reduction 202 is also formed in the hollow wire 200 to provide the desired discontinuity. A bottom mass 203 is added below the cut with an adhesive 206 to further exaggerate the discontinuity. The bottom mass 203 is preferably made of platinum.

FIG. 11B shows a side view of another embodiment of a wire with a discontinuity similar to FIG. 11A. This embodiment has a top mass 208 added adjacent to the cut 202 with an adhesive 206 to further exaggerate the discontinuity. The top mass 208 is preferably made of platinum, and the adhesive 206 can be epoxy or cyanoacrylate. Alternatively, the mass may be affixed by a welded or soldered connection.

FIG. 11C is a side view of a hollow wire 200 made, for example, of stainless steel, to allow therapeutic fluid or drugs to pass through to a target body site. A plurality of top masses 210 are attached adjacent to the cut 202 with an adhesive 212 to further exaggerate the discontinuity. The plurality of masses 210 are preferably made of platinum. It will be apparent that the wire of FIG. 11C could be alternatively formed with a plurality of bottom masses attached below the cut 202 in the hollow wire 200, in the manner of FIG. 11A.

5 The hollow wire can also be formed without through-cuts to provide a hollow detachment site that does not allow fluids to escape from the lumen of the hollow wire. As shown in FIG. 12A, a hollow wire 200 with a central lumen 214 is formed with an annular cut 216, or alternatively a pair of oppositely disposed straight cuts, forming a discontinuity, that does not extend to the lumen. A coil 218 which wraps around the outside of wire 200 is disposed adjacent cut 216 and attached with adhesive 220, to exaggerate the effect of the discontinuity. Alternatively, as shown in FIG. 12B, a coil 222 may be disposed within lumen 214 of the wire, adjacent the cut 216.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
10235
10240
10245
10250
10255
10260

spaced from the plurality of cuts 326 by a distance greater than the spacing between the cuts 326, and are provided to serve as the discontinuity for rupturing or fatigue when a vibrational signal is applied to the wire 302. The cuts 322, of course, could be formed at the same time the other cuts 326 are being formed but, would be made deeper or wider, to sever or rupture when the vibrational signal is applied to the wire 302.

FIG. 14 is a side cross sectional view of the catheter 304 and guide wire 302 combination with a wide cut 322 to allow fluid to pass through the cuts 322 and out the hollow distal end section 312. The terminal end of the wire 302 is tapered and inserted into the distal end section 312 at the proximal side of the end section 312, and secured by an adhesive 310. A coil 308 is soldered 306 or otherwise attached to the terminal end of the wire 302 and functions as a mechanical interlock for the adhesive bond 310 between the wire 302 and the end section 312. A plurality of cuts 326 are formed in the end section 312 extending generally transversely to shape the end section into a coiled or tangled configuration. Two or more cuts 322 are shown spaced from the plurality of cuts 326 by a distance greater than the spacing between the cuts 326, and are provided to serve as the discontinuity for rupturing when a vibrational signal is applied to the wire 302. A fatigue area 328 shown in FIG. 14 ruptures when high-frequency mechanical or ultrasonic energy passes through it.

Therapeutic fluid is delivered to a target body location through the catheter 304. The fluid passes through the catheter 304 and into the wide cuts 322. The therapeutic fluid is retained within the catheter 304 due to the slip fit of the catheter containment

sleeve 314 just past the wide cuts 322. A fluid passage 324 is formed between the platinum masses 318 in the end section 312 to allow fluid to flow out the distal end 313. The platinum masses 318 are attached to the inside of the distal end 312 with an adhesive 320. Upon completion of the site specific fluid or drug delivery, an ultrasonic transducer is used to fatigue the wide cut 322. Upon the localized fracture of the wide cut 322, the delivery section of the device 300 can be removed. The catheter containment sleeve 314 slides off the wire end 313 via a hydrophilic interface 316, and this leaves the wire end 313 inside the body. The catheter 304 and the guide wire 302 are then removed.

Naturally, it will be desirable for a user of this invention to know immediately when the end section of a wire has been detached from the wire so that the wire can be withdrawn from the body passageway. For each of the embodiments described above involving a delivery wire portion and an end section for ultimate detachment at a target site, the combinations of wire and end sections all have natural or resonant frequencies. Thus, when vibrational energy is applied to a wire, such as wire 16 in FIG. 1, the resonant frequency of the combination of the wire 16 and end section 16a will have a certain resonant frequency which can be detected by conventional spectrum analysis methods.

Figure 15A depicts a system for monitoring and displaying this resonant frequency, and for determining when detachment has occurred. This system shown in FIG. 15A is consistent with, but more detailed than that shown in FIG. 1. The system generally comprises an ultrasonic transducer 400 connected to a detachable coil device 16 having a detachable end section 16a, a spectrum analyzer 28, a frequency generator 24,

and a power amplifier 402. The ultrasonic transducer 400 is driven with a periodic waveform produced by the frequency generator 24 and amplified by the power amplifier 402. The electrical impedance, z (a complex ratio of voltage to current flow) of the transducer is a function of frequency, and of the physical device driven by the transducer (the detachable coil device 16). The impedance of the transducer is measured by the spectrum analyzer 28 as shown, or alternatively, may be measured by any other suitable electronic device, such as a microcontroller which is made for that purpose.

The spectrum analyzer 28 sweeps the frequency input to the transducer 400 while measuring the voltage v and current i to the transducer to generate a plot of impedance z versus frequency, which is displayed on a CRT screen 406 associated with the spectrum analyzer. Two exemplary plots of impedance versus frequency are given in FIGS. 15B and 15C as they would appear on CRT screen 406. These plots show impedance (z) versus frequency before and after detachment, respectively. It will be apparent that the plot of impedance versus frequency exhibits resonant peaks. As shown in FIG. 15B, when the coil device is unaltered, it may exhibit a resonant peak 404 at 60 KHz, for example. However, when the physical nature of the load on the transducer changes, i.e. the coil detaches, the resonant peak 404 shifts to the right of 60 KHz as shown in FIG. 15C.

Consequently, by observing the resonant frequency display on the analyzer 28, a user can obtain instantaneous information as to when the end section 16a has detached from the wire device 16. As an alternative or addition to visual observation of the

impedance versus frequency plot, an indicator lamp, and audible alarm, a secondary indication on the CRT screen, or any other means of providing a discernable signal to the user could be employed which would create a discernable signal only when detachment occurs.

5

In the manner described, a method and apparatus have been provided by which an end section of a wire may be easily, reliably and quickly detached from the delivery portion of the wire, generally without pain to the subject. The detached end section may be in the form of a coil, mass or other device and may be deposited in vasculature passageways or other body passageways. Vibrational energy is used to rupture discontinuities separating the delivery portion of the wire from the end section and so no electrical current of any kind is required, making it much safer for the subject.

It is to be understood that the above-described arrangements are only illustrative of the application of the principles of the present invention. Numerous modifications and alternative arrangements may be devised by those skilled in the art without departing from the spirit and scope of the present invention and the appended claims are intended to cover such modifications and arrangements.